

Digital Thermometer

PT-1 Digital Thermometer

Stainless steel sensing tip, direct measuring, pen style, wide measuring range, applied to refrigerant, heating and food processing etc...

Technical parameter:
Measuring range: $-50^{\circ}\text{C} \sim +300^{\circ}\text{C}$ ($-58^{\circ}\text{F} \sim +572^{\circ}\text{F}$)
Resolution: 0.1
Accuracy: $\pm 1^{\circ}\text{C}$ ($-20^{\circ}\text{C} \sim +80^{\circ}\text{C}$), $\pm 3^{\circ}\text{C}$ (other range)
Power: DC1.5V button battery
Product Dia: 20mm
Probe size: Dial 3.5mm,Length:110mm(L)
Switch between $^{\circ}\text{C}$ and $^{\circ}\text{F}$
Auto power off



PT-1

PT-2 Digital Thermometer

Pen style, stainless steel sensing tip, direct measuring, Portable, wide measuring range, High precision probe, Switch between $^{\circ}\text{C}$ and $^{\circ}\text{F}$, Data hold function, Used for food or cooking

Technical Parameter:
Temp. Measuring range: $-50^{\circ}\text{C} \sim +150^{\circ}\text{C}$ ($-58^{\circ}\text{F} \sim +302^{\circ}\text{F}$)
Operation Temperature: $-20^{\circ}\text{C} \sim +50^{\circ}\text{C}$ ($-4^{\circ}\text{F} \sim +122^{\circ}\text{F}$)
Resolution: 0.1
Accuracy: $\pm 1^{\circ}\text{C}$ ($10^{\circ}\text{C} \sim +150^{\circ}\text{C}$), $\pm 3^{\circ}\text{C}$ (other range)
Sensor Tip Length: 70mm
Auto power off



PT-2

PT-3 Digital Thermometer

Stainless steel sensing tip, direct measuring, portable, wide measuring range, Switch between $^{\circ}\text{C}$ and $^{\circ}\text{F}$, Applied to refrigerant, heating and food processing etc...

Technical parameter:
Measuring range: $-50^{\circ}\text{C} \sim +300^{\circ}\text{C}$ ($-58^{\circ}\text{F} \sim +572^{\circ}\text{F}$)
Resolution: 0.1
Accuracy: $\pm 1^{\circ}\text{C}$ ($-20^{\circ}\text{C} \sim +80^{\circ}\text{C}$), $\pm 5^{\circ}\text{C}$ (other range)
Power: DC1.5V AG5 button battery
Product Diameter: 34mm
Sensor Tip Length: 120mm
Sensor Tip Diameter: 3.8mm
IC operating environment: $-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$



PT-3

PT-4 Digital Thermometer

Pen style, stainless steel sensing tip, direct measuring, portable, Wide measuring range Applied to refrigerant, heating and food processing etc... Power saving: auto-off after 45 minutes no operation, Switch between $^{\circ}\text{C}$ and $^{\circ}\text{F}$, MIN/MAX memory, Data HOLD function for convenient reading

Technical parameter:
Measuring range: $-50^{\circ}\text{C} \sim +300^{\circ}\text{C}$ ($-58^{\circ}\text{F} \sim +572^{\circ}\text{F}$)
Resolution: 0.1
Accuracy: $\pm 1^{\circ}\text{C}$ ($-20^{\circ}\text{C} \sim +100^{\circ}\text{C}$), $\pm 5^{\circ}\text{C}$ (other range)
Power: DC1.5V LR44 button battery
Sensor Tip Length: 125mm



PT-4